

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : HYDRAULIC HVI B-15  
Product code : 33041  
Type of product : Lubricants  
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Industrial use, Professional use, Consumer use  
Use of the substance/mixture : Hydraulic oil

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Oman Lubricants  
Mandenmakerstraat 21-25  
2984 AS Ridderkerk  
Nederland  
T 0031 (0)10-4140046  
info@oman-lubricants.nl - www.oman-lubricants.nl

#### 1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Cardiff Centre) Gwenwyn Ward, Llandough Hospital	Penarth CF64 2XX Cardiff	+0344 892 0111	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aspiration hazard, Category 1 H304  
Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

May be fatal if swallowed and enters airways.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



# HYDRAULIC HVI B-15

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

	GHS08
Signal word (CLP)	: Danger
Hazardous ingredients	: Distillates (petroleum), hydrotreated light paraffinic; Distillates (petroleum), hydrotreated heavy paraffinic; Distillates (petroleum), hydrotreated light naphthenic
Hazard statements (CLP)	: H304 - May be fatal if swallowed and enters airways.
Precautionary statements (CLP)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P301+P310+P331 - IF SWALLOWED: Immediately call a doctor. Do NOT induce vomiting. P405 - Store locked up. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Comments : Highly refined mineral oils and additives.

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Distillates (petroleum), hydrotreated light naphthenic (Note L)	(CAS-No.) 64742-53-6 (EC-No.) 265-156-6 (EC Index-No.) 649-466-00-2 (REACH-no) 01-2119480375-34	≥ 80	Asp. Tox. 1, H304
2,6-di-tert-butylphenol	(CAS-No.) 128-39-2 (EC-No.) 204-884-0 (REACH-no) 01-2119490822-33	< 1	Skin Irrit. 2, H315 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Methyl methacrylate substance with a Community workplace exposure limit substance with national workplace exposure limit(s) (GB, IE)	(CAS-No.) 80-62-6 (EC-No.) 201-297-1 (EC Index-No.) 607-035-00-6 (REACH-no) 01-2119452498-28	< 0,1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1B, H317 STOT SE 3, H335

Comments : \* contains one or more of the following CAS-numbers (REACH registration numbers):  
64741-88-4 (01-2119488706-23), 64741-89-5 (01-2119487067-30), 64741-95-3 (01-2119487081-40), 64741-96-4 (01-2119483621-38), 64741-97-5 (01-2119480374-36),  
64742-01-4 (01-2119488707-21), 64742-52-5 (01-2119467170-45), 64742-53-6 (01-2119480375-34),  
64742-54-7 (01-2119484627-25), 64742-55-8 (01-2119487077-29), 64742-56-9 (01-2119480132-48),  
64742-57-0 (01-2119489287-22), 64742-62-7 (01-2119480472-38), 64742-65-0 (01-2119471299-27), 64742-71-8 (01-2119485040-48),  
72623-85-9 (01-2119555262-43), 72623-86-0 (01-2119474878-16), 72623-87-1 (01-2119474889-13),  
74869-22-0 (01-2119495601-36)  
The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346.

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.  
Full text of H-statements: see section 16

# HYDRAULIC HVI B-15

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Take off immediately all contaminated clothing. Rinse skin with water/shower. Repeated exposure may cause skin dryness or cracking.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Do not induce vomiting. Call a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: No additional information available. Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after ingestion	: Risk of lung oedema. May result in aspiration into the lungs, causing chemical pneumonia.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour. Combustible liquid.
Explosion hazard	: May form flammable/explosive vapour-air mixture.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.

#### 5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.
------------------	---

##### 6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area.
----------------------	----------------------------

##### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

# HYDRAULIC HVI B-15

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapours are flammable.
Precautions for safe handling	: Provide good ventilation in process area to prevent formation of vapour.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment.
Storage conditions	: Keep container closed when not in use. Keep in a cool, well-ventilated place away from heat.
Incompatible materials	: Heat sources.
Storage temperature	: 0 – 40 °C

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

HYDRAULIC HVI B-15	
EU - Occupational Exposure Limits	
Exposure limits/standards for materials that can be formed when handling this product. When mists/aerosols can occur the following is recommended	5 mg/m <sup>3</sup> - ACGIH TLV (inhalable fraction).

Methyl methacrylate (80-62-6)	
EU - Occupational Exposure Limits	
Local name	Methyl methacrylate
IOELV TWA (ppm)	50 ppm
IOELV STEL (ppm)	100 ppm
Regulatory reference	COMMISSION DIRECTIVE 2009/161/EU
Ireland - Occupational Exposure Limits	
Local name	Methyl methacrylate
OEL (8 hours ref) (ppm)	50 ppm
OEL (15 min ref) (ppm)	100 ppm
Notes (IE)	IOELV (Indicative Occupational Exposure Limit Values), Sens. (In the workplace respiratory or dermal exposures to sensitising agents may occur. Sensitizers may evoke respiratory or dermal reactions, e.g. asthma, rhinitis and allergic contact dermatitis. The notation does not distinguish between respiratory or dermal sensitisation. Chemical agents that are sensitizers present special problems in the workplace. Should an employee become sensitised, subsequent exposure may cause intense responses, even at low exposure concentrations well below the OELV. Exposure should be eliminated or significantly reduced through control measures such as engineering and process controls and use of personal protective equipment (PPE))
Regulatory reference	Chemical Agents Code of Practice 2020

# HYDRAULIC HVI B-15

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### United Kingdom - Occupational Exposure Limits

Local name	Methyl methacrylate
WEL TWA (mg/m <sup>3</sup> )	208 mg/m <sup>3</sup>
WEL TWA (ppm)	50 ppm
WEL STEL (mg/m <sup>3</sup> )	416 mg/m <sup>3</sup>
WEL STEL (ppm)	100 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

### 8.2. Exposure controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### Materials for protective clothing:

Wear suitable protective clothing

#### Hand protection:

Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Reusable gloves	Nitrile rubber (NBR)	6 (> 480 minutes)	≥ 0.35		EN ISO 374

#### Eye protection:

Safety glasses

Type	Use	Characteristics	Standard
Safety glasses	Droplet	clear	EN 166

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s):



#### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light yellow.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available

# HYDRAULIC HVI B-15

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: -60 °C - ASTM D5950 (pour point)
Boiling point	: No data available
Flash point	: 152 °C - ASTM D92 (COC)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable liquid and vapour.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 0,888 kg/l (15 °C) - ASTM D4052
Solubility	: Water : Practically not miscible.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: 15,6 mm <sup>2</sup> /s (40 °C) - ASTM D7279
Viscosity, dynamic	: No data available
Explosive properties	: Presents no particular fire or explosion hazard.
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

VOC content : 0 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Reacts violently with (strong) oxidizers.

### 10.4. Conditions to avoid

Open flame. Overheating. Heat. Sparks.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

No decomposition if stored normally.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

2,6-di-tert-butylphenol (128-39-2)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

# HYDRAULIC HVI B-15

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)	
LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rabbit	> 2000 mg/kg bodyweight
LC50 inhalation rat (Dust/Mist - mg/l/4h)	> 5,53 mg/l/4h

Skin corrosion/irritation	: Not classified
Additional information	: Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.

HYDRAULIC HVI B-15	
Viscosity, kinematic	15,6 mm <sup>2</sup> /s (40 °C) - ASTM D7279

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

2,6-di-tert-butylphenol (128-39-2)	
EC50 Daphnia	0,45 mg/l (Daphnia magna, freshwater, 48h)
EC50 72h algae (1)	1,4 mg/l (Selenastrum capricornutum, freshwater)

Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)	
LC50 fish	> 100 mg/l (96 h)
EC50 Daphnia	> 10 g/l
EC50 72h algae (1)	> 100 mg/l
NOEC (acute)	≥ 100 (72h)

### 12.2. Persistence and degradability

2,6-di-tert-butylphenol (128-39-2)	
Biodegradation	5 % Sturm (28 d)

Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)	
Persistence and degradability	Not readily biodegradable. Inherently biodegradable.

# HYDRAULIC HVI B-15

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### 12.3. Bioaccumulative potential

#### 2,6-di-tert-butylphenol (128-39-2)

Partition coefficient n-octanol/water (Log Kow)	4,5 Octanol/water (0,1 d)
---	---------------------------

#### Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)

Bioaccumulative potential	Bioaccumulative potential.
---------------------------	----------------------------

### 12.4. Mobility in soil

#### Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)

Ecology - soil	Insoluble in water.
----------------	---------------------

### 12.5. Results of PBT and vPvB assessment

#### Component

Distillates (petroleum), hydrotreated light naphthenic (64742-53-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
---	---

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods	: Do not allow into drains or water courses. Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Handle empty containers with care because residual vapours are flammable.
European List of Waste (LoW) code	: 13 01 10* - mineral based non-chlorinated hydraulic oils

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Not applicable



# HYDRAULIC HVI B-15

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

### Transport by sea

Not applicable

### Air transport

Not applicable

### Inland waterway transport

Not applicable

### Rail transport

Not applicable

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

Reference code	Applicable on
3.	2,6-di-tert-butylphenol
3(b)	HYDRAULIC HVI B-15 ; 2,6-di-tert-butylphenol ; Distillates (petroleum), hydrotreated light naphthenic
3(c)	2,6-di-tert-butylphenol

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 0 %

#### 15.1.2. National regulations

No additional information available

## 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

**For the following substances of this mixture a chemical safety assessment has been carried out**

Distillates (petroleum), hydrotreated light naphthenic

## SECTION 16: Other information

### Indication of changes:

Section	Changed item	Change	Comments
2.2	Precautionary statements (CLP)	Modified	
4.1	First-aid measures after ingestion	Modified	
4.1	First-aid measures general	Modified	
16	Abbreviations and acronyms	Modified	

### Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road

# HYDRAULIC HVI B-15

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
vPvB	Very Persistent and Very Bioaccumulative
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
EC-No.	European Community number
EN	European Standard
OEL	Occupational Exposure Limit
SDS	Safety Data Sheet
WGK	Water Hazard Class

Full text of H- and EUH-statements:	
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.

# HYDRAULIC HVI B-15

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

---

H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.