



OMAN HIGHWAY 10W40

Description

Highway 10W40 is a modern, all-round motor oil based on high quality solvent refined mineral and synthetic base oils. By adding a well balanced choice of additives the following properties are obtained:

- a lower fuel consumption
- a high and stable viscosity index
- a fast cold start
- a strong resistance against oxidation
- a very good detergency and dispersion
- a safe lubrication film at high temperatures
- a very strong protection against wear, corrosion and foaming
- a very low oil consumption

Application

Highway 10W40 An all-round, fuel economy motor oil based on semi-synthetic base oils and is recommended for use in gasoline- and diesel engines, with or without turbocharging, in passenger cars and delivery vans. This motor oil is developed for automobiles (< year 2002) that ask a high quality oil composition.

Specifications

ACEA A3/B3/B4 | API SL/CF | MB 229.1 | VW 501 01/505 00

Typical Characteristics

Density 15° C	kg/m ³	862
Viscosity, 40 °C	mm ² /s	90,1
Viscosity, 100°C	mm ² /s	13,8
Viscosity index	-	155
Flash Point, COC	°C	220
Pour Point	°C	-33
TBN	mg KOH/g	8.0
Sulphate Ash	%mass	1,0

Version : 1.0

Date : October 2020

Mentioned product values are indicative typical values. Oliemaatschappij Anglo Nederland B.V. can not be held responsible for any printing or typographical errors. On all our transactions our general delivery and sales conditions apply.